<u>TDR-12B</u> Tri-Deck Roller Finishing Mower

Value + Performance

Progressive's 12 foot Tri-Deck Roller Mower (TDR-12B) is designed to maintain wide area mowing venues that require a superlative after cut appearance. The superior quality of cut, coupled with the TDR-12's rugged construction, ease of maintenance and use give the TDR-12B the versatility to tackle a wide variety of mowing applications in parks, sports fields, and corporate campuses.

The **TDR-12's** full length rollers, which allow the mower to cut as low as $\frac{1}{2}$ " while simultaneously rolling and striping the mowing surface. Higher mowing speeds are often possible as the bounce from pneumatic tires are eliminated, making quick work of big jobs. Cutting heights are quick and simple to set with the supplied tool to any height from $\frac{1}{2}$ " to 4".

The **TDR-12B** is another example of the ingenuity and quality that goes into producing a durable, reliable rotary finishing mower that is easy to maintain. The **TDR-12B** is not only a Value and Performance leader, it is **"The Better Built Choice".**



The Better Built Choice."

TDR-12B Tri-Deck Roller Finishing Mower Features and Benefits

A superior cut:

With a tip speed over 18,000 feet per minute, our high lift blades provide superior vacuum to stand grass up to be cut cleanly and then evenly discharged over the rear rollers.

Provides a clean even cut at ground speeds of up to 6 miles per hour depending upon conditions.

Easy to use and maintain:

Maintenance Free Blade Spindles are used to both lower cost and time of routine maintenace. They also provide peace of mind that a missed greasing won't render the mower out of service. Mower adjusts quickly for multiple mowing height applications, with infinite cutting height adjustment from $\frac{1}{2}$ " to 4".

If the mower needs to be transported on public roads, optional fenders are available (shown). All pivot points are fitted with easy to reach grease fittings, making servicing the TDR-12B fast and simple.

<u>Pro Lift-N-Turn™</u>

Progressive's exclusive Pro Lift-N-Turn[™] system is standard equipment. Operators have the ability to slightly raise the decks off the ground with the PTO still engaged, making turning easier on the turf as the weight of the mower is distributed between the tractor and the floatation tires. An automatic stop prevents the main decks from raising too far.

TDR-12B Tri-Deck Finishing Mower Specifications

Two P275 / 60 SR 15 automotive tires (standard)

Part Number: Cutting width: Mowing Capacity*: TDR-12B 528712B 12 feet 2 mph 2.9 acres / hour 4 mph 5.8 acres / hour 6 mph 8.7 acres / hour 24" uncut circle Recommended PTO HP: Weight: Transport Width: Transport Height: Transport Length: 25-40 3,400 lbs 7 feet 7.5 feet 14 feet

Turning Radius:2Transport Tires:T*Assumes no overlap or turning

Under our policy of continuous improvement, we reserve the right to change specifications and designs without prior notice. The illustrations shown do not necessarily represent the standard version of product offered by Progressive Turf Equipment Inc

(800) 668-8873 (519) 527-1080 FAX: (519) 527-2275 www.progressiveturfequip.com info@progressiveturfequip.com





